



RECOMMENDED PCB LAYOUT

麦拉片

REV. (版本号)	DESCRIPTION (变更说明)	DATE (日期)	APPD (审核)

规格说明: Specifications:

电气特性: Electrical:

1. 额定电流: Current Rating
1.0A/contact terminal
2. 额定电压: Voltage Rating
30V DC
3. 接触阻抗: Contact Resistance
50 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:
300 V AC AT Sea Level
5. 绝缘阻抗: Insulation Resistance:
100MEGA ohms MIN

原材料: Raw material:

1. 塑胶: Plastic cement:
High Temperature Thermoplastics,
LCP Black
 2. 端子: Contact: Copper Alloy C2680/C5191
 3. 外壳: Shell: SPCC/Copper Alloy C2680
- 电镀: Electroplate:
1. 端子: Contact: Plated Gold in Mating Area;
Tin On Solder Tails
 2. 外壳: Shell:
Nickel Plating

深圳市金航标电子有限公司 www.BDS666.COM		页码 (SHEET)	1/1	单位 (UNIT): MM
型号: KH-MINI-SMT-5P-Cu	0755-83044319	版本 (REV)	A0	比例 (SCALE): 1:1
品名 (ITEM NO)	MINI USB 5P/F SMT B型 (0.3T, 0.6T)	日期 (DATE)	2009.11.16	公差 未注公差 (UNLESS INDICATED) I I ±0.30 I II ±0.20 I III ±0.10 I IV ±0.15 I V ±0.10 I VI ±0.10 I VII ±0.10 I VIII ±0.10 I IX ±0.10 I X ±0.10 I XI ±0.10 I XII ±0.10 I XIII ±0.10 I XIV ±0.10 I XV ±0.10 I XVI ±0.10 I XVII ±0.10 I XVIII ±0.10 I XIX ±0.10 I XX ±0.10 I XXI ±0.10 I XXII ±0.10 I XXIII ±0.10 I XXIV ±0.10 I XXV ±0.10 I XXVI ±0.10 I XXVII ±0.10 I XXVIII ±0.10 I XXIX ±0.10 I XXX ±0.10
料号 (PART NO)	PMBFB-X21D-XXX	设计 (DESIGN)		
图号 (DWG NO)	P-MBF-144 (2B-1)	审核 (CHECKED)		
		核准 (APPROVED)		