



RECOMMENDED P.C.B PATTERN LAYOUT

规格说明: Specifications:

电气特性: Electrical:

1. 额定电流: Current Rating  
1.5A/contact termi
2. 额定电压: Voltage Rating  
30V DC
3. 接触阻抗: Contact Resistance  
30 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:  
500 V AC AT Sea Lev
5. 绝缘阻抗: Insulation Resistance:  
1000MEGA ohms MIN

物理性能: Mechanical:

1. 插拔力: Connector Mate and Unmate Force  
Mate force: 3.57kgf(MA)  
Unmate force: 1.02kgf(MIN)
2. 端子保持力: Terminal Retention  
1.2kgf(MIN)

原材料: Material:

1. 塑胶: Housing:  
Hing Temperature Ternermap  
PBT White/Black
  2. 端子: Contact: Copper Alloy C2680
  3. 外壳: Shell: Copper Alloy C2680/SPCC
- 电镀: Finish:
1. 端子: Contact: Plated Gold in Mating Area  
Tin On Solder Talls
  2. 外壳: Shell:  
Nickel Plating

深圳市金航标电子有限公司

WWW.BDS666.COM

KH-2AF180-14.2JB

0755-83044319

UNLESS OTHERWISE  
SPECIFIED TOLERANCE

.X	±0.20
.XX	±0.15

DRAWN  
H.Q.huocv  
APPROVED

UNIT  
MM  
SCALE

TITLE USB AF 双层直插14.2I  
PART NO.