



SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 100V AC, DC
- 3、Temperatuer Range: -25°C ~ +85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000mΩ Min
- 6、Withstanding Voltang: 800V AC/minute
- 7、Material:Housing:Nylon66, UL94V-0

| 编 号 | 尺寸 (mm) | |
|-----------|---------|-------|
| | A | B |
| A2026-02Y | 2.00 | 6.00 |
| A2026-03Y | 4.00 | 8.00 |
| A2026-04Y | 6.00 | 10.00 |
| A2026-05Y | 8.00 | 12.00 |
| A2026-06Y | 10.00 | 14.00 |
| A2026-07Y | 12.00 | 16.00 |
| A2026-08Y | 14.00 | 18.00 |
| A2026-09Y | 16.00 | 20.00 |
| A2026-10Y | 18.00 | 22.00 |
| A2026-11Y | 20.00 | 24.00 |
| A2026-12Y | 22.00 | 26.00 |
| A2026-16Y | 30.00 | 34.00 |

| | | | | | | | | | | | | |
|-------------|---------------------|-------------|-------------------|-------------|---------------|----------------|----|----------------|-------------------|-------------|------------|---------------------|
| 制图 DRAWN | 变更内容 DESCRIPTION | 日期 DATE | GENERAL TOLERANCE | | 制图 DRAWING | 钱岳生 | | 料号 PART NO. | A2026-nY | | 版本 REV. | A |
| | | | X.±0.25 | X.*±2' | | 2014、10、20 | 品名 | | PA孔座 | 页次 SHEET | | 1/1 |
| | | | .X±0.20 | .X*±1' | | 审核 CHECK | 张名 | | 客户料号 CUTM. NO. | | | |
| | | | .XX±0.15 | .XX*±0.5' | | 核准 APPROVAL | 张名 | | 深圳市金航标电子有限公司 | | | www.kinghelm.com.cn |
| .XXX±0.10 | .XXX*±0.5' | 单位 UNITS | MM | 比例 SCALE | 1:1 | KH-A2026-06Y | | 0755-28190160 | | | | |