



编 号	尺寸 (mm)	
	A	B
A2015-2X02A	2.00	6.00
A2015-2X03A	4.00	8.00
A2015-2X04A	6.00	10.00
A2015-2X05A	8.00	12.00
A2015-2X06A	10.00	14.00
A2015-2X07A	12.00	16.00
A2015-2X08A	14.00	18.00
A2015-2X09A	16.00	20.00
A2015-2X10A	18.00	22.00
A2015-2X11A	20.00	24.00
A2015-2X12A	22.00	26.00
A2015-2X20A	38.00	42.00

SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltang: 800V AC/minute
- 7、Material: Wafer Nylon46, UL94V-0
PIN Brass Tin-plated

PCB LAYOUT

制图 DRAWN	变更内容 DESCRIPTION	日期 DATE	GENERAL TOLERANCE		制图 DRAWING	钱岳生		料号 PART NO.	A2015-2XnA		版本 REV.	A
			X.±0.25	X.*±2'		2021、05、03		品名	SPH直针		页次	1/1
			.XX±0.20	.X'±1'	审核	2021、05、04	张名	TITLE	WAFER DIP TYPE		SHEET	
			.XX±0.15	.XX'±0.5'	核准		张名	客户料号 CUTM. NO.				
			.XXX±0.10	.XXX'±0.5'	APPROVAL	2021、05、05		深圳市金航标电子有限公司		www.kinghelm.com.cn		
					单位 UNITS	MM	比例 SCALE	1:1	KH-A2015-2X02A		0755-28190160	