



| 编 号         | 尺寸 (mm) |       |
|-------------|---------|-------|
|             | A       | B     |
| A2015-2X02A | 2.00    | 6.00  |
| A2015-2X03A | 4.00    | 8.00  |
| A2015-2X04A | 6.00    | 10.00 |
| A2015-2X05A | 8.00    | 12.00 |
| A2015-2X06A | 10.00   | 14.00 |
| A2015-2X07A | 12.00   | 16.00 |
| A2015-2X08A | 14.00   | 18.00 |
| A2015-2X09A | 16.00   | 20.00 |
| A2015-2X10A | 18.00   | 22.00 |
| A2015-2X11A | 20.00   | 24.00 |
| A2015-2X12A | 22.00   | 26.00 |
| A2015-2X20A | 38.00   | 42.00 |

SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltang: 800V AC/minute
- 7、Material: Wafer Nylon46, UL94V-0  
PIN Brass Tin-plated

PCB LAYOUT

| 制图<br>DRAWN | 变更内容<br>DESCRIPTION | 日期<br>DATE | GENERAL TOLERANCE |            | 制图<br>DRAWING  | 钱岳生        |             | 料号<br>PART NO.    | A2015-2XnA              |                     | 版本<br>REV.    | A   |
|-------------|---------------------|------------|-------------------|------------|----------------|------------|-------------|-------------------|-------------------------|---------------------|---------------|-----|
|             |                     |            | X.±0.25           | X.*±2'     |                | 2021、05、03 |             | 品名<br>TITLE       | SPH直针<br>WAFER DIP TYPE |                     | 页次<br>SHEET   | 1/1 |
|             |                     |            | .XX±0.20          | .X'±1'     | 审核<br>CHECK    | 2021、05、04 | 张名          | 客户料号<br>CUTM. NO. |                         |                     |               |     |
|             |                     |            | .XX±0.15          | .XX'±0.5'  | 核准<br>APPROVAL | 2021、05、05 | 张名          | 深圳市金航标电子有限公司      |                         | www.kinghelm.com.cn |               |     |
|             |                     |            | .XXX±0.10         | .XXX'±0.5' | 单位<br>UNITS    | MM         | 比例<br>SCALE | 1:1               | KH-A2015-2X15A          |                     | 0755-28190160 |     |